

Safety data sheet

according to 1907/2006/EC, Article 31 Printing date 08.12.2023 Version number 1 Revision: 08.12.2023 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier • Trade name: Aerosol Silber hitzefest (D) · (Article number) product ID.: REZ1261 · 1.2 Relevant identified uses of the substance or mixture and uses advised against · Application of the substance / the mixture: painting · Uses advised against No further relevant information available. · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim Tel.: 0049-(0)6269-95-20 E-mail: labor@kwasny.de · Further information obtainable from: Product safety department · 1.4 Emergency telephone number: Tel.:+49 6269 95 20 · national: National Poisons Information Service, Birmingham Tel.: 844 892 0111 · K-Nr. 0001 **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008 flame H222 Extremely flammable aerosol. Aerosol 1 H229 Pressurised container: May burst if heated.

Eye Irrit. 2 STOT SE 3 H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Page 1/11

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)



- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

· Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane (containing ≤ 0,1 % butadiene (203-450-8)) ♦ Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	10-<25%
		(Contd. on page 3)

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

		(Contd. of page 2
	butanone	10-<25%
	ethyl acetate 🗞 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<25%
	dimethyl ether 🗞 Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
	n-butyl acetate 🚸 Flam. Liq. 3, H226; ᡧ STOT SE 3, H336, EUH066	5-<10%
L	isobutane (containing ≤ 0,1 % butadiene (203-450-8)) Flam. Gas IA, H220; Press. Gas (Comp.), H280, EUH018	5-<10%
Reg.nr.: 01-2119471843-32-xxxx	EC927-241-2 Naphtha (petroleum), hydrotreated light (<0,1% benzene) Flam. Liq. 3, H226; SAsp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	5-<10%
L	aluminium 🚸 Flam. Sol. 1, H228	1-<2.5%
EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene, mixture of isomers Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	<1%
	methyl methacrylate Flam. Liq. 2, H225;	<0.1%
EINECS: 209-136-7 Reg.nr.: 01-2119529238-36-xxxx	octamethylcyclotetrasiloxane Flam. Liq. 3, H226; & Repr. 2, H361f; Aquatic Chronic 1, H410 (M=10) PBT; vPvB	<i>≥</i> 0.0025-<0.025%

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

 \cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 4)

GB

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
 6.2 Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
 6.3 Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Keep away from heat and direct sunlight. Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- 106-97-8 butane (containing ≤0,1 % butadiene (203-450-8))
- WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

(Contd. on page 5)

GB

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

	(Contd. of page 4
78-93-3 butanone	
WEL Short-term value: 899 mg/m ³ , 300 ppm	
Long-term value: 600 mg/m³, 200 ppm	
Sk, BMGV	
141-78-6 ethyl acetate	
WEL Short-term value: 1468 mg/m ³ , 400 ppm	
Long-term value: 734 mg/m ³ , 200 ppm	
115-10-6 dimethyl ether	
WEL Short-term value: 958 mg/m ³ , 500 ppm	
Long-term value: 766 mg/m ³ , 400 ppm	
123-86-4 n-butyl acetate	
WEL Short-term value: 966 mg/m ³ , 200 ppm	
Long-term value: 724 mg/m ³ , 150 ppm	
1330-20-7 xylene, mixture of isomers	
WEL Short-term value: 441 mg/m ³ , 100 ppm	
Long-term value: 220 mg/m ³ , 50 ppm	
Sk; BMGV	
80-62-6 methyl methacrylate	
WEL Short-term value: 416 mg/m ³ , 100 ppm	
Long-term value: 208 mg/m ³ , 50 ppm	
· Ingredients with biological limit values:	
78-93-3 butanone	
BMGV 70 μmol/L	
Medium: urine	
Sampling time: post shift	
Parameter: butan-2-one	
1330-20-7 xylene, mixture of isomers	
BMGV 650 mmol/mol creatinine	
Medium: urine	
Sampling time: post shift	
Parameter: methyl hippuric acid	
• Additional information: The lists valid during the making were used as basis.	
· 8.2 Exposure controls	
• Appropriate engineering controls No further data; see section 7.	
· Individual protection measures, such as personal protective equipment	
· General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing	
Wash hands before breaks and at the end of work.	

Avoid contact with the eyes. Avoid contact with the eyes and skin.

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

(Contd. on page 6) GB

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

(Contd. of page 5)

• Hand protection Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Penetration time of glove material

Gloves must be changed after every contamination.

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- \cdot For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
- butyl rubber, 0,7mm · Eye/face protection
- Safety glasses



Tightly sealed goggles

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical p General Information	1
Physical state	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	-44 °C
Flammability	Not applicable.
Lower and upper explosion limit	* *
Lower:	1.5 Vol % (106-97-8 butane (containing $\leq 0,1$ % butadiene (203-450-8)))
Upper:	11.5 Vol % (78-93-3 butanone)
Flash point:	<0 °C
Auto-ignition temperature:	235 °C (115-10-6 dimethyl ether)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	3,600 hPa (74-98-6 propane)
Density and/or relative density	
Relative density	0.747 g/cm^3
Vapour density	Not determined.

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

	(Contd. of page
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of heal	th and
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
	Not determined.
Solvent content:	
Organic solvents:	87.7 %
0	With propellant gas. Content given by weight.
VOC (EU)	(<840g/l)
	87.68 %
Solids content:	12.3 %
Change in condition	
Evaporation rate	Not applicable.
Information with regard to physical hazard c	lasses
Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised contained
	May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamme	,
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

GB

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

(Contd. of page 7)

List II; III

Trade name: Aerosol Silber hitzefest (D)

- · Serious eye damage/irritation Causes serious eye irritation.
- · STOT-single exposure May cause drowsiness or dizziness.

· 11.2 Information on other hazards

· Endocrine disrupting properties

556-67-2 octamethylcyclotetrasiloxane

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Ikke relevant.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- Additional ecological information:
- · General notes:
- Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number		
ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
IMDG	AEROSOLS	
IATA	AEROSOLS, flammable	
14.3 Transport hazard class(es)		
ADR		
Class	2 5F Gases.	

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D) (Contd. of page 8) 2.1 · Label · IMDG, IATA 2.1 Gases. · Class · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void not classified · 14.5 Environmental hazards: • Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Hazard identification number (Kemler code): not classified · EMS Number: F-D, S-USW1 Protected from sources of heat. · Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 · Segregation Code litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · 14.7 Maritime transport in bulk according to IMO instruments Not applicable. · Transport/Additional information: ·ADR \cdot Limited quantities (LQ) lLCode: E0 · Excepted quantities (EQ) Not permitted as Excepted Quantity · Transport category 2 · Tunnel restriction code D · IMDG · Limited quantities (LQ) lLCode: E0 • Excepted quantities (EQ) Not permitted as Excepted Quantity UN 1950 AEROSOLS, 2.1 · UN "Model Regulation":

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture VOC: <840g/l

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

(Contd. of page 9)

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

· Poisons Act

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

 \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

 \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

· Technical instructions (air):

ClassShare in %NK50-100

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. The safety data sheet may only be passed on to third parties for the manufacturer's brands.

· Relevant phrases

H220 Extremely flammable gas.

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

EUH018 In use may form flammable/explosive vapour-air mixture.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

• Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

(Contd. on page 11)

Printing date 08.12.2023

Version number 1

Revision: 08.12.2023

Trade name: Aerosol Silber hitzefest (D)

(0 1 0 10)
(Contd. of page 10)