

Page 1/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

· Article number: 2380, 2381, 2383, 2384

1.2 Relevant identified uses of the substance or mixture and uses advised against Void

· Application of the substance / the mixture Maintenance product

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Dr. O.K. Wack Chemie GmbH

Untere Au 9

DE-85107 Baar-Ebenhausen Tel.: +49 8453 41995-100 Mail: info@dr-wack.com www.dr-wack.com

· Further information obtainable from: Safety department

· 1.4 Emergency telephone number: During business hours: +49 8453 41995-501

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

(Contd. on page 2)



Page 2/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

(Contd. of page 1)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.`

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Contains Fatty acids, tall-oil, reaction products with boric acid (H3BO3) and diethanolamine. May produce an allergic reaction.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of the substances with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol Flam. Liq. 2, H225; Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	25-<35%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0	butane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<20%
CAS: 1569-01-3 EINECS: 216-372-4 Reg.nr.: 01-2119474443-37-xxxx	1-propoxypropan-2-ol Flam. Liq. 3, H226; Eye Irrit. 2, H319	10-<15%
CAS: 64742-94-5 EC number: 918-811-1 Index number: 649-424-00-3 Reg.nr.: 01-2119463583-34-xxxx	Hydrocarbons, C10 aromatics Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336, EUH066	5-10%
CAS: 91770-03-5 EINECS: 294-785-9 Reg.nr.: 01-2119961359-26-xxxx	Fatty acids, tall-oil, reaction products with boric acid (H3BO3) and diethanolamine Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B; H317: C ≥ 7 %	<3%
CAS: 28016-00-4 EINECS: 248-778-2 Reg.nr.: 01-2120130528-59-xxxx	Zinkbis-(dinonylnaphtalinsulfonat) Eye Dam. 1, H318; Skin Irrit. 2, H315	1-<3%

· SVHC None

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out into the fresh air.

(Contd. on page 3)



Page 3/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: After contact with skin, wash immediately with plenty of soap and water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Danger of bursting.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Avoid contact with skin and eyes.

Wear protective clothing.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Avoid contact with skin and eyes.

(Contd. on page 4)



Page 4/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

(Contd. of page 3)

Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs	thanal	
64-17-5 e		
Oral	DNEL system. effects (long-term)	87 mg/kg KG/Tag (consumer)
Dermal	DNEL system. effects (long-term)	206 mg/kg KG/Tag (consumer)
		343 mg/kg KG/Tag (worker)
Inhalative	DNEL system. effects (long-term)	114 mg/m³ (consumer)
		950 mg/m³ (worker)
	DNEL local effects (short-term)	950 mg/m³ (consumer)
		1,900 mg/m³ (worker)
1569-01-3	1-propoxypropan-2-ol	,
Oral	DNEL system. effects (long-term)	11 mg/kg KG/Tag (consumer)
Dermal	DNEL system. effects (long-term)	36 mg/kg KG/Tag (consumer)
		82.5 mg/kg KG/Tag (worker)
Inhalative	DNEL system. effects (long-term)	38 mg/m³ (consumer)
		263 mg/m³ (worker)
64742-94-	5 Hydrocarbons, C10 aromatics	1
Oral	DNEL system. effects (long-term)	7.5 mg/kg KG/Tag (consumer)
Dermal	DNEL system. effects (long-term)	7.5 mg/kg KG/Tag (consumer)
		12.5 mg/kg KG/Tag (worker)
Inhalative	DNEL system. effects (long-term)	32 mg/m³ (consumer)
	,	151 mg/m³ (worker)

(Contd. on page 5)



Page 5/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

		(Contd. of page	
28016-	00-4 Zinkbis-(dinonylnaphtalinsulfonat)	, , ,	
Dermal	Dermal DNEL system. effects (long-term) 0.316 mg/kg (consumer)		
Inhalati	ive DNEL system. effects (long-term) 2.23 mg/m³ (consumer)		
PNECs			
64-17-5	5 ethanol		
PNEC	0.79 mg/l (marine water)		
	580 mg/l (STP)		
	0.96 mg/l (fresh water)		
PNEC	0.63 mg/kg (soil)		
	3.6 mg/kg (sediment (freshwater))		
1569-0	1-3 1-propoxypropan-2-ol		
PNEC	0.1 mg/l (fresh water)		
28016-	00-4 Zinkbis-(dinonylnaphtalinsulfonat)		
PNEC	0.000023 mg/l (marine water)		
	10 mg/l (STP)		
	0.00023 mg/l (fresh water)		
PNEC	0.59 mg/kg (soil)		
	0.293 mg/kg (sediment (marine water))		
	2.93 mg/kg (sediment (freshwater))		

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Ensure good ventilation/exhaustion at the workplace.

Keep away from foodstuffs, beverages and feed.

Be sure to clean skin thoroughly after work and before breaks.

Avoid contact with the eyes and skin.

- Respiratory protection: Not necessary if room is well-ventilated.
- Hand protection

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

· Eye/face protection Safety glasses

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Yellow-brown
Product specific
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling

range -44 °C

· Flammability Not applicable.

Lower and upper explosion limit

Lower: 1.3 Vol %
 Upper: 15.0 Vol %
 Flash point: -97 °C
 Auto-ignition temperature: 365 °C

Decomposition temperature: Not determined.pH Not determined.

Viscosity:

· Kinematic viscosity
· Dynamic:

Not determined.

Not determined.

· Solubility

water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure at 20 °C: 8300 hPa

· Density and/or relative density

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void

(Contd. on page 7)



Page 7/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

V - 7.0 (replaces version 6.0) Printing date 22.05.2024 Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

		(Contd. of page 6
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: Store away from oxidising agents.
- 10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
64-17-5 et	thanol	
Oral	LD50	10,470 mg/kg (rat) (OECD Prüfrichtlinie 401)
Dermal	LD50	>2,000 mg/kg (rabbit) (OECD Prüfrichtlinie 402)
Inhalative	LC50/4 h	>20 mg/l (mouse)
		124.7 mg/l (rat) (OECD Prüfrichtlinie 403)
106-97-8	butane	
Inhalative	LC50/4 h	658 mg/l (rat)
1569-01-3	1-propox	ypropan-2-ol
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
	•	(Contd. on page 8



Page 8/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: \$100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

		(Contd. of page 7
64742-94-	5 Hydroca	arbons, C10 aromatics
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50	>2-20 mg/l (rat)
9003-13-8	Polyprop	ylenglykolmonobutylether
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
28016-00-	4 Zinkbis-	dinonylnaphtalinsulfonat)
Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>10,000 mg/kg (rabbit)
Inhalative	LC50/6 h	>7.6 mg/l (rat)

- · Specific symptoms in biological assay: Not determined
- Skin corrosion/irritation

No irritating effect.

Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity		
· Aquatic toxicity:		
64-17-5 ethanol		
LC50/96h	15,300 mg/l (Pimephales promelas)	
EC50/72h (static)	275 mg/l (Chlorella vulgaris) (OECD Prüfrichtlinie 201)	
LC50/24h	11,200 mg/l (Oncorhynchus mykiss)	
EC10/72h (static)	11.5 mg/l (Chlorella vulgaris) (OECD Prüfrichtlinie 201)	
NOEC/120h	250 mg/l (Danio rerio) (OECD Prüfrichtlinie 212)	
EC50/48h	>10,000 mg/l (Daphnia magna) (DIN 38412)	
LC50/48h (static)	5,012 mg/l (Ceriodaphnia dubia)	
	8,140 mg/l (Leuciscus idus)	
1569-01-3 1-prop	oxypropan-2-ol	
LC50/96h (static)	>100 mg/l (Oncorhynchus mykiss)	
EC50 (static)	3,800 mg/l (bacteria)	
		(Contd. on page



Page 9/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

	(Contd. of page 8		
LC50/48h (static)	>100 mg/l (Daphnia magna)		
64742-94-5 Hydr	64742-94-5 Hydrocarbons, C10 aromatics		
LC50	>1-≤10 mg/l (Fish)		
	>1-≤10 mg/l (algae)		
28016-00-4 Zinkl	bis-(dinonylnaphtalinsulfonat)		
EC0/48h	>0.2 mg/l (Daphnia magna)		

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation Disposal must be made according to official regulations.

· European waste catalogue				
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST			
16 05 00	gases in pressure containers and discarded chemicals			
16 05 04* gases in pressure containers (including halons) containing hazardous substances				

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number		
· ADR, IMDG, IATA	UN1950	
14.2 UN proper shipping name		
ADR	1950 AEROSOLS	
·IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	

(Contd. on page 10)



Page 10/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

	(Contd. of page
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDG, IATA	Void
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litr
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear
	of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre
	Segregation as for class 9. Stow "separated from" class
	except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1



Page 11/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

(Contd. of page 10)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- Date of previous version: 14.06.2023
- Version number of previous version: 6.0

(Contd. on page 12)



Page 12/12

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 22.05.2024 V - 7.0 (replaces version 6.0) Revision: 22.05.2024

Trade name: S100 DRY LUBE Kettenspray S100 Dry Lube Chain Spray

(Contd. of page 11)

· Abbreviations and acronyms:

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3