

Page 1/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: S100 125er Kettenspray
 S100 Chain Lube Sub-125cc
- · Article number: 2390
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against Void
- · Application of the substance / the mixture Maintenance product
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Dr. O.K. Wack Chemie GmbH

Untere Au 9

DE-85107 Baar-Ebenhausen Tel.: +49 8453 41995-100 Mail: info@dr-wack.com www.dr-wack.com

- · Further information obtainable from: Safety department
- · 1.4 Emergency telephone number: During business hours: +49 8453 41995-501

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS09

- · Signal word Danger
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated light

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

(Contd. on page 2)



Page 2/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: S100 125er Kettenspray S100 Chain Lube Sub-125cc

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable. · **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances with nonhazardous additions.

| · Dangerous components: | | |
|--|--|----------|
| CAS: 64742-49-0 EC number: 921-024-6 Index number: 649-328-00-1 Reg.nr.: 01-2119475514-35 | Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | ≥25-≤50% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 | propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 20-<25% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 | butane Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 20-<25% |

- · SVHC None
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

If symptoms persist consult doctor.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Hazards If swallowed or in case of vomiting, danger of entering the lungs.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

— E



Page 3/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: S100 125er Kettenspray S100 Chain Lube Sub-125cc

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Danger of bursting.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Avoid contact with skin and eyes.

· 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with skin and eyes.

Keep away from heat and direct sunlight.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from foodstuffs.

(Contd. on page 4)



Page 4/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: S100 125er Kettenspray S100 Chain Lube Sub-125cc

(Contd. of page 3)

· Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

| | ** *** · · · · · · · · · · · · · · · · | | | | |
|--|--|----------------------------------|----------------------|--|--|
| | DNELs 64742-49-0 Naphtha (petroleum), hydrotreated light | | | | |
| | | | | | |
| | Oral | DNEL system. effects (long-term) | 699 mg/kg (consumer) | | |
| | Dermal | DNEL system. effects (long-term) | 699 mg/kg (consumer) | | |
| | | | 773 mg/kg (worker) | | |
| | Inhalative | DNEL system. effects (long-term) | 608 mg/m³ (consumer) | | |
| | | | 2,035 mg/m³ (worker) | | |

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Ensure good ventilation/exhaustion at the workplace.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Safety glasses

ΕU



Page 5/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

-44 °C

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: \$100 125er Kettenspray

S100 Chain Lube Sub-125cc

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol

Light brown
Characteristic
Not determined
Undetermined

· Boiling point or initial boiling point and boiling

range

· Flammability Not applicable.

· Lower and upper explosion limit

Lower: 1.5 Vol %
Upper: 10.9 Vol %
Flash point: -97 °C
Auto-ignition temperature: 365 °C

Decomposition temperature: Not determined.

· pH Void

Viscosity:

Kinematic viscosityDynamic:Not determinedNot determined

Solubility

• water: Not miscible or difficult to mix.

• Partition coefficient n-octanol/water (log value) Not determined. • Vapour pressure at 20 °C: 8300 hPa

Density and/or relative density

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Heating may cause an explosion.

In use, may form flammable/explosive vapour-air

mixture.

· Change in condition

· Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

• Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

Oxidising gases
Gases under pressure
Flammable liquids
Flammable solids

(Contd. on page 6)



Page 6/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: \$100 125er Kettenspray

S100 Chain Lube Sub-125cc

| | | (Contd. of page 5 |
|---|------|-------------------|
| Self-reactive substances and mixtures | Void | |
| Pyrophoric liquids | Void | |
| Pyrophoric solids | Void | |
| Self-heating substances and mixtures | Void | |
| Substances and mixtures, which emit flamm | able | |
| gases in contact with water | Void | |
| Oxidising liquids | Void | |
| Oxidising solids | Void | |
| Organic peroxides | Void | |
| Corrosive to metals | Void | |
| Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

- 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: Store away from oxidising agents.
- 10.6 Hazardous decomposition products:

No decomposition if used and stored according to specifications.

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity Based on available data, the classification criteria are not met.

| LD/LC50 values relevant for classification: | 64742-49-0 Naphtha (petroleum), hydrotreated light | Oral | LD50 | >5,000 mg/kg (rat) | Dermal | LD50 | >2,000 mg/kg (rat) | Inhalative | LC50/4 h | >20 mg/l (rat) | 106-97-8 butane | Inhalative | LC50/4 h | 658 mg/l (rat)

- · Specific symptoms in biological assay: Not determined
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: S100 125er Kettenspray S100 Chain Lube Sub-125cc

(Contd. of page 6)

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information: Vapours may cause drowsiness and dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation Disposal must be made according to official regulations.

| · European | · European waste catalogue | |
|------------|--|--|
| 16 00 00 | WASTES NOT OTHERWISE SPECIFIED IN THE LIST | |
| 16 05 00 | gases in pressure containers and discarded chemicals | |
| 16 05 04* | 4* gases in pressure containers (including halons) containing hazardous substances | |

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN1950

(Contd. on page 8)



Page 8/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

 Printing date 13.08.2024
 V - 2.0 (replaces version 1.1)
 Revision: 13.08.2024

Trade name: S100 125er Kettenspray S100 Chain Lube Sub-125cc

| | (Contd. of page |
|---|--|
| 14.2 UN proper shipping name | |
| ADR | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS |
| IMDG | AEROSOLS (Naphtha (petroleum), hydrotreated light), MARINE POLLUTANT |
| IATA | AEROSOLS, flammable |
| 14.3 Transport hazard class(es) | |
| ADR | |
| Class | 2 5F Gases. |
| Label | 2.1 |
| IMDG, IATA | |
| Class | 2.1 Gases. |
| Label | 2.1 |
| 14.4 Packing group | |
| ADR, IMDG, IATA | Void |
| 14.5 Environmental hazards: | Product contains environmentally hazardous substances. Naphtha (petroleum), hydrotreated light |
| Marine pollutant: | Yes |
| | Symbol (fish and tree) |
| Special marking (ADR): | Symbol (fish and tree) |
| 14.6 Special precautions for user | Warning: Gases. |
| Hazard identification number (Kemler code): | - |
| EMS Number: | F-D,S-U |
| Stowage Code | SW1 Protected from sources of heat. |
| | SW22 For AEROSOLS with a maximum capacity of 1 litro |
| | Category A. For AEROSOLS with a capacity above 1 litre |
| | Category B. For WASTE AEROSOLS: Category C, Clear |
| | of living quarters. |
| Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 litre |
| | Segregation as for class 9. Stow "separated from" class |
| | except for division 1.4. |
| | For AEROSOLS with a capacity above 1 litre: |
| | Segregation as for the appropriate subdivision of class 2. |
| | For WASTE AEROSOLS: |
| | Segregation as for the appropriate subdivision of class 2. |
| 14.7 Maritime transport in bulk according to IM | |
| instruments | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E0 |
| _ | Not permitted as Excepted Quantity |
| Transport category Tunnel restriction code | 2 |
| | D |



Page 9/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 13.08.2024 V - 2.0 (replaces version 1.1) Revision: 13.08.2024

Trade name: \$100 125er Kettenspray

S100 Chain Lube Sub-125cc

(Contd. of page 8)

·IMDG

Limited quantities (LQ)

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 10)



Page 10/10

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

V - 2.0 (replaces version 1.1) Printing date 13.08.2024 Revision: 13.08.2024

Trade name: S100 125er Kettenspray S100 Chain Lube Sub-125cc

(Contd. of page 9)

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

- · Classification according to Regulation (EC) No 1272/2008 Calculation method
- · Date of previous version: 14.06.2023
- · Version number of previous version: 1.1
- · Abbreviations and acronyms:

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2